

FISHMAN FLUENCE™
Killswitch Engage - Signature Humbucker
HSS Wiring with SSA & SSP Single Width Pickups

Neck: SSP
Single Width Pickup

Middle: SSA
Single Width Pickup

Bridge: Ceramic
(or Alnico if preferred)

9V Battery

+3dB Boost Pads
(top side of PCB)
Bridge with solder
to activate.

(+) (-)

Ring

Sleeve

Output
Jack

Tip

Bridge
Ground

Voice-3 Wire
(Not Used)

Volume

25k

25k

.22uF

Tone
Pull for Bridge Voice-2

SSA Pickup - Wire Color Scheme

Red: +9V
White: SSA Coil(s) Out
Yellow: Preamp In
Green: Preamp Out
Blue: 2&4 Position Dual Single Mode (Position 4)
Black: 2&4 HB Tapped + Single Mode (Position 2)
Shield: GND

SSP Pickup

This is a passive pickup used in conjunction with the SSA active pickup and it's preamp.

Pickup Selector Function

1. Bridge Humbucker
2. Bridge Coil Tapped & Middle
3. Middle
4. Neck & Middle
5. Neck

Pickup Selector
5-Position
4P5T "Super Switch"

Neck Pickup

Bridge Pickup

