

FISHMAN FLUENCE™

Classic Humnucker w/ Middle SSA & Neck SSP

Master Volume

Master Tone - Pull for voice 2 (bridge only)

5-Way Schaller Megaswitch M

Neck: SSP
Single Width Pickup

Middle: SSA
Single Width Pickup

+3dB Boost Pads
(top side of PCB)
Bridge with solder
to activate.

Bridge Pickup

9V Battery

(+)

(-)

Output Jack

Ring

Sleeve

Tip

Bridge Ground

Volume

25k

25k

Tone
Pull for Voice-2
Positions 1

.22uF
"224"

SSA Pickup - Wire Color Scheme

Red: +9V
White: SSA Coil(s) Out
Yellow: Preamp In
Green: Preamp Out
Blue: 2&4 Position Dual Single Mode (Position 4)
Black: 2&4 HB Tapped + Single Mode (Position 2)
Shield: GND

SSP Pickup

This is a passive pickup used in conjunction with the SSA active pickup and its preamp.

5-Way Pickup Selector
Schaller Megaswitch M

Bat Positions

5 ← → 1

Selector Positions

1. Bridge
2. Bridge (tapped) w / Middle
3. Middle
4. Neck & Middle
5. Neck

* = wire is not used insulate or tape off